



Order Code : 3103201
 Product Code : STL 030A 40OD28 2K3 175TK3I LN6XMC

STL MIKRO

30 W Recessed Mounted Single Module
 Linear LED Luminaire



Product Data


Standard Features

Housing	: RAL 7047 Powder finished aluminium extrusion housing, aluminium injection cover
Diffuser	: Glare minimizing highly permeable diffuser
Ceiling Type	: Plasterboard
IP Grade	: IP40
Installation	: Recessed mounted
Light Source	: Mid Power LED

Optical & Electrical Features

Power Consumption	: 29.9 W
Final Luminous Flux	: 2327.7 lm
Efficacy	: 77.6 lm/W
Input Voltage	: 220-240 24V DC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -25 °C/+40 °C
Impact Resistance	: IK02
Led Life Time - L70	: > 60.000 hours @Ta= 40 °C

Optional Features

Correlated Color Temperatures	: 2700K, 3000K
Color Option	: RAL 9005



STL MIKRO

30 W Recessed Mounted Single Module Linear LED Luminaire

3103201 STL 030A 40OD28 2K3 175TK3I LN6XMC

Dimensions (mm)

	a	b	h1	h2	d ¹ , d ²
Single Module	1775	54	60	40	1766x45
Starting Module	1765	54	60	40	1758x45
Finishing Module	1765	54	60	40	1758x45
Intermediate Module	1755	54	60	40	1755x45



Weight (kg)

Standard	3,4
----------	-----

- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
www.eaeaydinlatma.com.tr

Revision date: 01.02.2019